

EWM LED Wall Pack 70W



Features

- Slim Design – lighter weight.
- Die cast aluminum, quality PC lens
- High Lumen Efficiency – 125-130 lumens per watt.
- Modular Design – easy to maintain
- UL/cUL, IP65 for wet locations

Ordering information

Family	Size	Watts	Driver	Lens	Beam	CRI	Color	Mount	Sort #
WP	MD	70=70W 40=40W	MIN Multi-volt, internal, non-dim	PC	FC fulli-cutoff	8 >80	30 3000K 40 4000K 50 5000K	S0 Surface Mount	100

Example: WP-LG-10-MIN-PCSC-850-S0-115

SPECIFICATIONS

WATTS	70W	40W
LUMENS	9100	5200
LUMENS PER WATT	130	130
BEAM ANGLE	Full Cutoff	
COLOR TEMPERATURES	3000K/4000K/5000K	
INPUT VOLTAGE	100-277V, (347-480V available)	
HERTZ	50-60hz	
CRI	>80	
LED L70 LIFETIME	50,000hrs	
MOUNTING OPTIONS	Surface Mount	
CONTROL OPTIONS	Photocell, dimming driver	
DIMENSIONS(mm)	18.5"x9.5"x9.0"	
WEIGHT		
CERTIFICATIONS	UL/cUL IP65	
WARRANTY	5 Years	

Photometric

